

**KSW 4 10/5,08 W 1-10****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Similar to illustration

KSW marking strips are used to identify multi-pole PCB plug-in connectors. Users can print them individually without being confined to a certain pitch.

- Smudge-proof labelling
- Strips 2.5 mm and 4 mm wide
- Simply stick on - finished
- Optimum adhesion
- PVC-free

**General ordering data**

|                     |   |
|---------------------|---|
| Version             | KSW, Terminal marker, 4 x 50.8 mm, Pitch in mm (P): 5.08 Weidmueller, white |
| Order No.           | <a href="#">1705820001</a>  |
| Type                | KSW 4 10/5,08 W 1-10  |
| GTIN (EAN)          | 4008 1909 1485 1  |
| Qty.                | 10 pc(s).   |
| Alternative product | <a href="#">1629930000</a>  |

Creation date September 29, 2022 3:47:15 PM CEST

Catalogue status 23.09.2022 / We reserve the right to make technical changes.

## KSW 4 10/5,08 W 1-10

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

### Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Height     | 4 mm    | Height (inches) | 0.157 inch |
| Width      | 50.8 mm | Width (inches)  | 2 inch     |
| Net weight | 0.9 g   |                 |            |

### Temperatures

|                             |        |
|-----------------------------|--------|
| Operating temperature range | 150 °C |
|-----------------------------|--------|

### General data

|                                   |                                |  |                  |
|-----------------------------------|--------------------------------|--|------------------|
| Adhesive                          | Acrylate                       | Application/manufacturer                     | Weidmueller      |
| Colour                            | white                          | Colour of printing                           | black            |
| Material                          | Polyester, PVC-free            | Material colour according to resistance code | 9                |
| Number of markers per combination | 1 Label reel = Terminal marker | Number per sheet                             | 20               |
| Operating temperature range       | 150 °C                         | Operating temperature range, max.            | 150 °C           |
| Orientation of print              | horizontal                     | Printed characters                           | Numbers          |
| Printing                          | 1 - 10                         | Printing method                              | Thermal transfer |
| Type of printing                  | Standard                       | Version                                      | Self-adhesive    |
| Width                             | 50.8 mm                        |  |                  |

### Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000761    | ETIM 7.0    | EC000761    |
| ETIM 8.0    | EC000761    | ECLASS 9.0  | 27-14-11-37 |
| ECLASS 9.1  | 27-14-11-37 | ECLASS 10.0 | 27-14-11-37 |
| ECLASS 11.0 | 27-28-11-01 | ECLASS 12.0 | 27-28-11-01 |

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                  |  |
|------------------|--|
| Engineering Data | <a href="#">EPLAN, WSCAD</a>             |
| Catalogues       | <a href="#">Catalogues in PDF-format</a> |