


# HSK-K

Item number 1209500050



## Technical data

<b>Material</b>	Polyamide V0 according to UL94
<b>Seal</b>	NBR
<b>Protection class</b>	IP 54 , IP 68 with additional O-ring:IP68 - 10bar/30min , IP 69 K
<b>Type Rating by</b>	12 , 4 , 4X , 6 (with additional O-ring) , UL 50E
<b>Temperature range</b>	-40°C to +100°C
<b>Colour</b>	grey
<b>RAL</b>	7035
<b>Variant</b>	Metric
<b>External thread (AG)</b>	M50 x 1,5
<b>Cable diameter</b>	32 - 38 mm
<b>Thread length (GL)</b>	13 mm
<b>Height (H)</b>	49 mm
<b>Wrench size (SW1/SW2)</b>	60/60 mm
<b>Tightening torque</b>	15 Nm



# HSK-K

Item number 1209500050

## Commercial data

Packaging Unit	5
EAN code	4033878411599
Weight	0.08825 kg
ETIM 7	EC000441
ETIM 8	EC000441
ETIM 9	EC000441
eCl@ss 10.1	27-14-44-32
Customs tariff number	39269097

Note:



Dimensions and specifications may be changed without prior notice



[www.hummel.com](http://www.hummel.com)