


# HSK-K-MZ-Ex

Item number 1215200150



## Technical data

<b>Material</b>	Polyamide
<b>Seal</b>	NBR
<b>Material o-ring</b>	NBR
<b>Protection class</b>	IP68 - 10bar/30min , IP 69 K
<b>Ex-protection level</b>	II 1D Ex ta IIIC Da , II 2G Ex eb IIC Gb
<b>Temperature range</b>	-20°C to +70°C
<b>Colour</b>	black
<b>RAL</b>	9005
<b>Variant</b>	Metric
<b>External thread (AG)</b>	M20 x 1,5
<b>Cable diameter</b>	7 - 12 mm
<b>Thread length (GL)</b>	15 mm
<b>Height (H)</b>	35.5 mm
<b>Wrench size (SW1/SW2)</b>	24/24 mm
<b>Wrench size (SW1/SW2)</b>	24/24
<b>Tightening torque</b>	3.5 Nm

# HSK-K-MZ-Ex

Item number 1215200150

## Commercial data

Packaging Unit	50
EAN code	4033878412008
Weight	0.02111 kg
ETIM 7	EC000441
ETIM 8	EC000441
ETIM 9	EC000441
eCl@ss 10.1	27-14-44-34
Customs tariff number	39269097

## Note:

