


HSK-K

Item number 1219200050



Technical data

| | |
|------------------------------|---|
| Material | Polyamide V0 according to UL94 |
| Seal | NBR |
| Protection class | IP 54 , IP 68 with additional O-ring:IP68 - 10bar/30min , IP 69 K |
| Type Rating by | 12 , 4 , 4X , 6 (with additional O-ring) , UL 50E |
| Temperature range | -40°C to +100°C |
| Colour | grey |
| RAL | 7035 |
| Variant | Metric |
| External thread (AG) | M20 x 1,5 |
| Cable diameter | 10 - 14 mm |
| Thread length (GL) | 9 mm |
| Height (H) | 28 mm |
| Wrench size (SW1/SW2) | 27/27 mm |
| Tightening torque | 4.5 Nm |



HSK-K

Item number 1219200050

Commercial data

| | |
|-----------------------|---------------|
| Packaging Unit | 50 |
| EAN code | 4033878413142 |
| Weight | 0.01342 kg |
| ETIM 7 | EC000441 |
| ETIM 8 | EC000441 |
| ETIM 9 | EC000441 |
| eCl@ss 10.1 | 27-14-44-32 |
| Customs tariff number | 39269097 |

Note:



Dimensions and specifications may be changed without prior notice



www.hummel.com