



Similar to illustration

Our extensive range of TM sleeves is suitable for all-purpose use. They cover a wide range of applications: from thin conductors to cables with large external diameters. This range offers printed inlay tags with maximum protection against outside influences. TM sleeves permit flexible installation.

- Optimum protection for printed inlay tags
- Wide range of applications for conductors and cables
- One tag type for all cross-sections
- TMX 30 for mounting with cable ties (width 4.6 mm)

General ordering data

| | |
|------------|------------------------------------------------------------------------|
| Version | TM, Socket x 9 mm, PVC, Colour: Transparent, Conductor O.D.: 6 - 10 mm |
| Order No. | 1806360000 |
| Type | TM 204/20 V0 |
| GTIN (EAN) | 4032248275878 |
| Qty. | 500 items |

Technical data

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Dimensions and weights

| | | | |
|------------|--------|-----------------|-------------|
| Depth | 9 mm | Depth (inches) | 0.3543 inch |
| Height | 20 mm | Height (inches) | 0.7874 inch |
| Width | 9 mm | Width (inches) | 0.3543 inch |
| Net weight | 0.72 g | | |

Temperatures

| | |
|-----------------------------|-------------|
| Operating temperature range | -40...80 °C |
|-----------------------------|-------------|

Environmental Product Compliance

| | |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC | No SVHC above 0.1 wt% |

General data

| | | | |
|-----------------------------------|-------------|-----------------------------------|---------------------------|
| Type of printing | neutral | Width | 9 mm |
| UL 94 flammability rating | V-0 | Operating temperature range, max. | 80 °C |
| Operating temperature range, min. | -40 °C | Colour | Transparent |
| Basic material | PVC | Recommended industries | Transportation, Machinery |
| Operating temperature range | -40...80 °C | | |

Conductor and cable markers

| | | | |
|-------------------------------|--------------------|----------------------------------|------------------------|
| Conductor cross-section, max. | 16 mm ² | Conductor cross-section, min. | 6 mm ² |
| Conductor O.D., max. | 10 mm | Conductor O.D., min. | 6 mm |
| Conductor O.D. | 6 - 10 mm | Cross-section for connected wire | 6 - 16 mm ² |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC001530 | ETIM 9.0 | EC001530 |
| ETIM 10.0 | EC001530 | ECLASS 14.0 | 27-28-11-02 |
| ECLASS 15.0 | 27-28-11-02 | | |