

## DEK 5/8 PLUS FSZ 31-40

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

[www.weidmueller.com](http://www.weidmueller.com)



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

### General ordering data

|            |  |
|------------|--|
| Version    | Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00 Weidmueller, white |
| Order No.  | <a href="#">2748050000</a>   |
| Type       | DEK 5/8 PLUS FSZ 31-40   |
| GTIN (EAN) | 4050118891485  |
| Qty.       | 800 items  |

**DEK 5/8 PLUS FSZ 31-40**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

**Technical data**

**Approvals**

ROHS Conform

**Dimensions and weights**

|            |        |                 |             |
|------------|--------|-----------------|-------------|
| Height     | 5 mm   | Height (inches) | 0.1968 inch |
| Width      | 8 mm   | Width (inches)  | 0.315 inch  |
| Net weight | 0.08 g |                 |             |

**Temperatures**

Operating temperature range -40...100 °C

**Environmental Product Compliance**

|                          |                             |                  |  |
|--------------------------|-----------------------------|------------------|--|
| RoHS Compliance Status   | Compliant without exemption |                  |  |
| REACH SVHC               | No SVHC above 0.1 wt%       |                  |  |
| Product Carbon Footprint | Cradle to gate              | 0,001 kg CO2 eq. |  |

**General data**

|                                      |                               |           |  |
|--------------------------------------|-------------------------------|-----------|--|
| Orientation of print                 | vertical                      |           |  |
| Width                                | 8 mm                          |           |  |
| UL 94 flammability rating            | V-2                           |           |  |
| Operating temperature range, max.    | 100 °C                        |           |  |
| Operating temperature range, min.    | -40 °C                        |           |  |
| Colour                               | white                         |           |  |
| Halogen                              | No                            |           |  |
| Basic material                       | Polyamide 66                  |           |  |
| Colour of printing                   | black                         |           |  |
| Printed characters                   | Numbers                       |           |  |
| Number of markers per packaging unit | Form of supply                | MultiCard |  |
| Number of markers per combination    | 1 MultiCard = Terminal marker |           |  |
| Operating temperature range          | -40...100 °C                  |           |  |
| Application/manufacturer             | Weidmueller                   |           |  |

**Connector markers**

Pitch in mm (P) 8.00 mm

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 8.0    | EC000761    | ETIM 9.0    | EC000761    |
| ETIM 10.0   | EC000761    | ECLASS 14.0 | 27-28-11-01 |
| ECLASS 15.0 | 27-28-11-01 |             |             |

**Drawings**



**Drawing**

